abode

Diagon single lever

Product Finish: Stainless steel	**Product code:** AT1105 **EAN13 barcode:** 5060048382488

Product features:

• 304 grade brushed stainless steel construction

• Single lever control for effortless single handed control

• Modern minimalism with flair

• Antisplash spout supplied as standard

• Supplied compete with flexible tail pipes for fast simple fitting

Additional information / Parts included:

Product dimensions:

DIAGON STEEL
SINGLE LEVER

abode

(c) abode home products ltd
www.abode.eu

our policy is to continually
improve and develop products,
and accordingly we reserve the
right to amend specifications
without prior notice

• **Overall Height / projection:** 323 mm
• **Exit reach:** 206 mm
• **Exit height:** 178 mm
• **Centre distance(s):**

• **Base diameter(s):** 64 x 45mm
• **Recommended hole diameter:** Ø 35 mm
• **Max. surface depth:** 40 mm

• **Spout diameter:** 22 mm
• **Spout aerator size:** 16f

Packaged properties:

Box length: 420mm	**Box depth:** 75mm
Box width: 240mm	**Units per outer:** 5
Tap only weight: 1.08kg	**Boxed weight:** 1.82kg

Product flow characteristics:

• **Min / Max water pressure:** 0.50 / 5.5 bar
• **Recommended / Max water temperature:** 46°C / 70°C
• **Part G - Mixed flow rate at 3 bar (litres / min):** 11.03

• **Control valve type:** Single lever ceramic cartridge
• **Product flow characteristics:** Single flow
• **Non return valve(s):** Hot & cold (separate)

• **Aerator type:** Metal fine mesh diffuser
• **Accepts revolve / spray areator:** No
• **Spout connection method:** Grub screw

• **Tail pipe inlet / outlet size:** M10 / 1/2" BSP Female
• **Inlet pipe type / length:** flexible stainless braided hose / 400 mm

---

Care instructions summary:
- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):
- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year